

# Window Options

## Oxford Range



Traditional Oxford



County Oxford



Sunburst Oxford



Horizon Oxford



Waterton Oxford



Cascade Oxford



Canterbury Oxford



Traditional Oxford



County Oxford



Sunburst Oxford



Horizon Oxford



Waterton Oxford



Cascade Oxford



Canterbury Oxford

## Hampton Range



Traditional Hampton



County Hampton



Sunburst Hampton



Horizon Hampton



Waterton Hampton



Cascade Hampton



Canterbury Hampton



Traditional Hampton



County Hampton



Sunburst Hampton



Horizon Hampton



Waterton Hampton



Cascade Hampton



Canterbury Hampton

N.B. Please confirm with office regarding window configurations in relation to door width.

# Colours

## Polyester Colour Selections



White



Racing Green




Black



Vandyke Brown

## Laminate Colour Selections



Golden Oak



Rosewood

Other colour selections are available upon request

Please Note: Colours shown are as close as possible to actual products as printing allows. We strongly recommend comparing with actual samples.



Aluminium profiled rail, incorporating weatherseal strip, on the bottom of the door prevents undesirable material from entering your garage.

## European Standards Conformance Characteristics

### Air Permeability - EN12426

Safe-T-Glide® single skin doors NT  
Insul-Glide® 42mm insulated doors Class 3

### Resistance to Water Penetration - EN12425

Safe-T-Glide® single skin doors NT  
Insul-Glide® 42mm insulated doors Class 3, 150Pa

### Resistance to Wind Load - EN12424

Safe-T-Glide® single skin doors Class 2, 570Pa  
Insul-Glide® 42mm insulated doors Class 5, 1100Pa



## Glidermatic® GTS OPTIMA® Technical Information

Premium Sectional Overhead Door Operator

<b>Pulling Force</b> - Torque	1000N belt, 600N chain
<b>Motor</b>	Powerful 370 watts, 24V DC motor
<b>Transformer</b>	High efficiency - 175 VA
<b>Courtesy Light</b>	Environment friendly LED illumination
<b>Drive Mechanism</b>	Quiet belt and chain (NGTS 2000)
<b>Soft Start / Soft Stop</b>	Yes - 150mm before reaching both upper & bottom limits
<b>Radio Frequency</b>	868 MHz
<b>Code</b>	Rolling code technology
<b>Wall Control</b>	Yes - external push button option
<b>Battery Back-Up</b>	Yes - 1000Ah recommended
<b>Accessory Power Output</b>	Yes - 12V
<b>Rated Door Area</b> - Max	21m <sup>2</sup> max
<b>Rated Door Weight</b> - Max	200Kg max belt, 150 kg chain
<b>Manual Release</b>	New easy pull mechanism
<b>Power Off</b>	Auto sensing door distance
<b>Auto Close</b>	Yes - 90 seconds