



Door Operators ➤ Automatically the best choice

[www.linkcontrols.co.uk](http://www.linkcontrols.co.uk)

## NEW Range - Comfort 360, 370, 380

Operator Model	Push & Pull Force (N)	Door Travel Speed (mm/s)	Power Input Standby (W)	Illuminant	Extendable to
<b>Comfort 360</b>	650	220	<0.6 W <b>blue</b> line	2 x 10 LED : 80 W	160 W
<b>Comfort 370</b>	850	235	<0.6 W <b>blue</b> line	2 x 10 LED : 80 W	160 W
<b>Comfort 380</b>	1100	180	<0.6 W <b>blue</b> line	2 x 10 LED : 80 W	160 W



**blue**line



[E] EASY  
[O] OPERATING  
[S] SYSTEM

MSBUS

More functions. More clarity. More speed. More light.  
More performance. More design. Less energy consumption.



**blue**line



[E] EASY  
[O] OPERATING  
[S] SYSTEM

MSBUS

Flexible installation with a power head that can be rotated

[E] EASY  
[O] OPERATING  
[S] SYSTEM

One for all

Marantec operator systems are activated using the uniform programming structure. This saves time and simplifies the installation of different operators.



Width: 48 mm  
Height: 88 mm  
Depth: 14 mm  
Weight: 0,08 kg

**blue**line



More speed (up to 235 mm/sec)  
and less energy consumption at once

**MSBUS**

External programming device Command 108  
with 3 m connecting cable with BUS connector

### Marantec BUS-System

- Easy cabling with coded system plug
- Self-detection(plug and play) of connected modules
- Permanent function control of all BUS devices
- Easy function programming either directly on the control or with the external programming device
- Central failure notification of all moduls on the control



Completely integrated battery back-up system  
(Optional extra)