

TECKENTRUP | HOME



# TECKENTRUP 62 SWING SECURE.

The secure & stylish swing garage door for your home.



Teckentrup 62 Swing Secure  
is Secured by Design as  
standard

**Secured by Design**



Police Preferred Specification



Tested to  
LPS 1175 Issue 8  
A1 (SR1)

# STYLISH, SECURE A CLASSIC, UPDATED



## TECKENTRUP 62-1 SWING SECURE

Single leaf versions for side access to your garage.

## TECKENTRUP 62-2 SWING SECURE GARAGE DOOR

Double leaf versions provide easy access and performance comparable to your front door.






Our doors are independently tested and certified to EN14351-1 and all current safety legislation and carry a CE mark.

#### A NEW AND SECURE LOOK FOR GARAGES

The main entrance doors to homes are becoming more attractive and high performance. Hinged swing garage doors, whilst still popular, are limited in choice and performance.

The Teckentrup 62 Swing Secure brings crisp aesthetics and comparable performance to the main entrance door; Thermal Transmittance, Resistance to Windload, Watertightness, Air Permeability and Operating Forces are all certified in these high performance doors.

Add to this, certified security to the Secured by Design Police Preferred Specification as standard, tested to LPS 1175 Issue 8 A1 (SR1) and Teckentrup 62 Swing Secure garage doors are a classic, updated for today's homes. The superb build quality of the double leaf doors is complemented by matching single leaf doors for side or rear access to your garage space.



Tested to LPS 1175  
Issue 8 A1 (SR1)



**TECKENTRUP**  
DOOR SOLUTIONS

HOME | OPTIONS

# Style Your Door



Stainless Steel Lever Handle



## HANDLES

A stainless steel lever handle and security keyed cylinder is the standard configuration for all doors.

Stainless steel pull handles in two lengths can also be added in singles or pairs to add a striking contemporary look to your door.



1200mm 'D' Handle



1200mm 'D' Handle Pair



1500mm 'D' Handle



1500mm 'D' Handle Pair





**Colours**White  
RAL 9016Anthracite Grey  
RAL 7016Jet Black  
RAL 9005

Doors can also  
be coloured to  
any RAL shade.

**Hinge Options**

KO hinges are supplied as  
standard and are matched to  
the door colour.

Stainless steel hinges are  
available as an option.



KO Hinge

Stainless  
Steel Hinge**Security**

Certified security to The Secured  
by Design Police Preferred  
Specification as standard.




Tested to LPS 1175 Issue 8 A1 (SR1)

**High Grade Window Options**

All window units are laminated glass and available with  
clear glazing for vision or satin glazing to allow light in  
with privacy.

Doors with windows are supplied with a lock cylinder that  
can only be operated by key from outside and inside to  
maintain security. Should a glazing element be breached in  
an attempt to enter, the door cannot be opened (an internal  
thumb turn is not available).



Glazing sizes:  
230mm x 1360mm  
300mm x 300mm  
300mm diameter

Windows are supplied  
with Anodised Aluminium  
surrounds with concealed  
fixings.

**Glazing Styles**

Clear




Satin




TALL 1360 V1




TALL 1360 V2




Square 300 S



Square 300 SP



Square 300 S2




Square 300 S2P




Square 300 S3




Square 300 S3P




Round 300 R




Round 300 RP




Round 300 R2



Round 300 R2P



Round 300 R3



Round 300 R3P

Guarantee: All doors  
have a 2 year guarantee  
against mechanical  
defects and a 10 year  
guarantee against  
perforation of the door  
panel. Terms and  
conditions apply, visit  
[www.teckentrup.co.uk](http://www.teckentrup.co.uk)  
for details.

# 2/10

2/10 Year Guarantee

# HIGH QUALITY BUILT TO LAST



## U VALUE 1.4 Wm<sup>2</sup>K\*

The U value of the door confirms its insulation capability. The value is for a complete door with frame and is exceptionally low (which is good!).

**\*U value includes a 3mm clearance gap under the door and does not apply to doors with windows.**



### Automatic Quality

Every Teckentrup 62 Swing Secure is made to order in our automated production facility that operates to quality procedures audited to BS EN ISO 9001: 2008. We care about the environment too - this is why all of our products are certified in accordance with the Environmental Product Declaration (EPD).



### Certified Performance

The door and frame are CE marked and have been independently tested to have the following impressive characteristics:

#### Insulation (Thermal Transmittance)

EN 13241-1 B: 1.4 Wm<sup>2</sup>K (door without windows)

#### Resistance to Windload

EN 12424:Class 2

#### Watertightness

EN 12425:Class 2

#### Air Permeability

EN 12426:Class 2

#### Operating Forces

EN 12604: 150N

#### Operating Cycles

EN1191 C5 (200,000)

#### Security

Secured by Design Police Preferred Specification

#### Secured by Design



Police Preferred Specification



Tested to  
LPS 1175 Issue 8  
A1 (SR1)

## Security



Each door is supplied with a pair of Security keys. Security keys add extra security by preventing unauthorised copying. They cannot be cut by anyone other than the issuer of the key - Teckentrup.



The inactive leaf is secured with flush bolts to the top and bottom of the leaf.



Doors are independently certified for security to the Secured by Design Police Preferred Standard, tested to LPS 1175 Issue 8 A1 (SR1).

## Threshold

For improved weather protection, a stepped aluminium threshold with a bulb weather strip is provided. The door leaves close against the raised weather strip creating an improved barrier to dust and debris. The threshold is DDA compliant for wheelchair access.



## Hold Open Stays


Double doors have foot activated stays to hold the door in the open position.



**Please note - stays are not designed for high wind applications.**

## Rain-guard

An anodised aluminium rain-guard is supplied with all doors to help limit water ingress at the top of the door.



## Frames

Every door is supplied with a frame. A 'block frame' is the standard option with two variants, the 'Corner Frame' and the 'Corner Counter Frame'. Each frame is made from heavy gauge corrosion protected steel and provides a stable platform for the door to operate.



### Block Frame

The block frame is the standard frame design. Provided with Rockwool filling.


### FB Profile Option



### Corner Frame

The innovative corner frame wraps around the front corner of the garage opening providing a neat edge. Its slim profile also gives an additional 56 mm drive through width compared to a block frame.

Requires back-filling with a foam sealant.



### Corner Counter Frame

The counter frame wraps around the front and back corner of the garage opening providing a neat edge. Its slim profile also gives an additional 56mm drive through width compared to a block frame.

Requires back-filling with a foam sealant.

The FB Frame option allows for a flush finish between door lip, frame and wall finish on Corner and Corner Counter frames in new openings that are rendered after the door is installed. The FB option also provides a flush finish on block frames that are fixed at the front edge of the garage opening reveal.

HOME | PROFILE

Teckentrup is a family business with operations throughout the world. In the UK we make our garage doors in Warrington, Cheshire. CarTeck Automatic is available through a national network of independent Garage Door Specialist installers.

Teckentrup offers more than garage doors: We provide solutions and have set three quality standards for our garage doors:

# Design. Security. Service.



December 2020

Teckentrup UK Limited, Units 2-4 Opus 9 Industrial Estate,  
Woburn Road, Winwick Quay, Warrington WA2 8UE


t: 01925 924 050

f: 08701 314 843

e: sales@teckentrup.co.uk

**TECKENTRUP**  
DOOR SOLUTIONS

## Design



**We combine ease of use with aesthetics.**

Good design uses innovative technology to make using a product intuitive and effortless. CarTeck Automatic sectional garage doors offer a wide range of design options that will transform the look of your home and the way you use your garage space.

## Safety & Security



**We combine security with safety.**

Our products are designed to provide peace of mind with both physical security and the knowledge that durability and safe operation are inherent.

## Service



**We combine speed with reliability.**

The Teckentrup team and our network of Garage Door Specialists installers love to make your new door a pleasure to own. From planning to installation. You'll always receive expert advice and the best service for installation, maintenance and aftercare.

## Quality & Environment

Teckentrup operates to quality procedures audited to ISO 9001. We care about the environment too - this is why our products are certified in accordance with the Environmental Product Declaration (EPD).

ISO 14001 Environmental Management

ISO 50001 Energy Management



Member



**WWW.TECKENTRUP.CO.UK**