



DexxoPro

1 system for all Garage Doors
With the Dexxo Pro system from Somfy, you have a motorisation system suitable for the majority of door types.

1 system for all Doors up to 15m²



Canopy doors*



Sectional doors



Swing doors



Retractable doors

2 rail systems for all requirements

Chain rail in 2 lengths –
2.9M and 3.5M



Belt rail in 2 lengths –
2.9M and 3.5M



Dexxo Pro garage door operator



The new Somfy garage door operator designed to provide a hard-wearing and reliable system for garage door professionals.



100% compliant

Dexxo Pro has been tested to ensure complete compliance with the relevant safety legislation:

- Dexxo Pro meets with the required safety standards for door and gate motorisation – EN60335-2-95
- When installed correctly, Somfy motors comply 100% with European standards – EN13241-1 and EN12453
- ITT certificates of incorporation and compliance certificates issued by independent agencies are available at www.somfy.com/ce




Dexxo Pro garage door operator



Up and running in 90 seconds flat!



All remote controls are memorised by the motor and an initial self-learning cycle of open/close is performed to record all the settings (end-of-travel, speed, power) – all in just 4 clicks!



Self-learning cycle: 80 seconds

Control programming: 10 seconds



Pivoting head for installations where space is confined



The rail can be fixed direct to the ceiling



A range of accessories can be connected using the removable terminal block

Your customers are unique, so Dexxo Pro has a range of different settings. Programming is simple and user-friendly, enabling you to add the finishing touch to your work and enhance your service.

13 parameter settings:

- P0 : Operating mode
- P1 : Safety warning light
- P2 : Safety accessory input
- P3 : Obstacle detection sensitivity
- P4 : Partial or vent opening
- P5 : Closing speed
- P6 : Partial/vent open position
- P7 : Docking speed when closing
- A0 : Safety action before opening
- A1 : Safety action when closing
- A2 : Obstacle detection when closing
- T0 : Automatic closing time delay
- T1 : Lighting time delay

Everything you need to tailor your solution to each individual customer's needs



An LCD interface with:

- drop down menu browsing
- feedback from actions in progress
- diagnostic aid
- event history

For easy installation and maintenance

- Select parameter
- Launch self learn cycle & validate selection and parameter values
- Change parameter values & manual operation mode
- Trigger self learning & enter/exit settings menu
- Memorise remote controls

Dexxo Pro garage door operator



Product specification





Each motor head kit is supplied with:



- Motor head with integrated electronics
- 2 x Keytis 2 RTS remote controls
- 230Vac 40W E14 lamp
- 1M pre-connected mains supply cable
- Rail + head installation accessories
- Installation and user guide

Motor selection

Up & Over doors



Sectional doors



Characteristics	Dexxo Pro 800	Dexxo Pro 1000
Mains power supply	230Vac	
Motor power supply	24Vdc	
Max. power consumption on standby	5W	
Max. power consumption in operation	350W	
Door area	9m ²	15m ²
Traction force	80kg	100kg
Minimum height under lintel	35mm	
Integrated light	230Vac 40W E14 lamp	
External light connection	230Vac 500W (max)	
Operating temperature	-20°C / +60°C	
Radio frequency	433.42 MHz	
Maximum number of handsets	32	

Dexxo Pro is controlled by Somfy RTS technology, which means that it is fully interoperable with the existing range of motor and control systems.



It has been tested to 90,000 cycles, which is equal to 50 operations per day for 5 years. Our confidence in the Dexxo Pro build quality is reinforced with a 5 year warranty.

