

Garage door operators ProMatic



Note:

Installation of photocell is required for impulse control without view of the door or if the automatic timer is activated!

The garage door operator ProMatic cannot be used on sectional doors LPU67!



ProMatic

Series 3

ProMatic
Battery
Series 2

Operator head

Article no.

4512584

4512598

		FS 10 1-part	FS 2 2-part	FS 10 1-part	FS 2 2-part
Complete set prices for operator head with side guide	K – short boom	—	—	—	—
	M – medium boom	—	—	—	—
	L – long boom	—	—	—	—

Product description

Door cycles (Open / Close)	Per day/per hour	12 / 5		5 / 2	
Suitable for:	• The Industrial sector	—		—	
	• Doors with wicket door/timber doors ²⁾	— / ● Timber doors with max. 3.5 m door width and 9 m ² door leaf surface		— / —	
	• Max. door width	5000		3000	
	• Max. door leaf surface	11.25 m ²		8 m ²	

Operator data

Motor	24 V DC gear drive			
Mains voltage	230 V – 240 V AC		Technical data on the battery see page 486	
Power input	0.2 kW			
Pull and push force	600 N		350 N	
Peak force	750 N		400 N	
Opening speed ¹⁾	max. 14 cm/s		max. 13 cm/s	
Standby	< 7 watt		< 0.1 watt	

Housing

	Plastic, galvanized steel base plate			
Temperature range	–20 °C to +60 °C		–15 °C to +45 °C	
Protection category	Only for dry rooms			

Control electronics

Impulse control	●		●	
Power limit	●		●	
Adjustable soft start and soft stop	●		●	
Display	LED		LED	
Adjustable operator light and partial opening	— / ●		—	
Adjustable automatic timer	●		—	
Hold-open phase after activation	30 s.		—	